

# SPECIFICATIONS

## QUIK-STOP TRASH FREE™

### THERMAL BREAK



601 North Main Street | PO Box 468 | Madison, NE 68748  
800.255.0776 | thermaldesign.com

**Tired of chasing trash around your job site?**  
**The solution is Quik-Stop Trash Free™**

#### QUIK-STOP TRASH FREE™ THERMAL BREAK

Quik-Stop Trash Free™ thermal break is an insulative foam tape that is placed on to the joists, purlins or girts to help minimize the conductive paths between the metal panels and the building structure.

Quik-Stop Trash Free may be used on the interior or exterior flanges. Adhesive film is located on the inside of the tape roll allowing installer to easily unroll and apply to framing. Quik-Stop Trash Free eliminates the need to peel and remove the paper backing and time consuming project site clean up. Applies easily to clean and dry surfaces. Works great in retrofit applications.

#### PHYSICAL DIMENSIONS

QUIK-STOP TRASH FREE™ THERMAL BREAK	ROLL LENGTH	WIDTH	THICKNESS	QUANTITY
	100'	Nominal 3"	3/16"	12 per box

~2.8" wide, other sizes are available on special order. Colors may vary.

Quik-Stop™ and Quik-Stop Trash Free™ are trademarks licensed to Thermal Design, Inc and Simple Saver Services, LLC.


#### QUIK-STOP TRASH FREE™ THERMAL BREAK



Quik-Stop Trash Free on the exterior flange (above).



PURLINS



GIRTS



#### Specification Values

Specification values are typical data subject to normal manufacturing variations and are not meant to be guaranteed or limiting specifications. Thermal Design, Inc. reserves the right to improve and change component specifications without notice. The information and performance values contained in this document replace and supersede all other previous documents created and managed by Thermal Design, Inc.